



Ball-lock cable ties made of AISI 304 stainless steel, provide excellent resistance to high temperatures, corrosion and extraordinary resistance to UV radiation. These cable ties are very easy to install.

EXAMPLE USE:

- fixing of cables and pipes in shipbuilding, petrochemical plants, offshore platforms and fire risk environments
- „electrical safety” markings in identification label installation (e.g. fire extinguishing system) which must be maintained in the event of fire
- installations where high mechanical and UV resistance is required

The ties can be fastened manually or with a dedicated tool. The ties have rounded edges to increase safety during application and protect against damage to the electrical cable insulation.

TECHNICAL DATA

Material:	AISI 304 stainless steel
Material flammability:	non-flammable
Moisture absorption:	not applicable
Operating temperature:	-80 °C ÷ +538 °C
Resistance:	moderate resistance to acids, seawater, oils, greases, chemicals, solvents. High UV resistance.

SIZE CHART

Steel grade	Length [mm]	Width [mm]	Bundle diameter [mm]	Tensile strength [kg]	Packaging [pcs]
AISI 304	1200	7,9	360	81	100
AISI 304	1050	7,9	310	81	100
AISI 304	850	7,9	255	81	100
AISI 304	750	7,9	191	81	100
AISI 304	600	7,9	154	81	100
AISI 304	500	7,9	143	81	100
AISI 304	400	7,9	102	81	100
AISI 304	350	7,9	89	81	100
AISI 304	300	7,9	76	81	100
AISI 304	200	7,9	50	81	100

Steel grade	Length [mm]	Width [mm]	Bundle diameter [mm]	Tensile strength [kg]	Packaging [pcs]
AISI 304	1200	4,5	360	61	100
AISI 304	1050	4,5	310	61	100
AISI 304	850	4,5	255	61	100
AISI 304	750	4,5	191	61	100
AISI 304	650	4,5	175	61	100
AISI 304	550	4,5	160	61	100
AISI 304	500	4,5	143	61	100
AISI 304	400	4,5	102	61	100
AISI 304	350	4,5	89	61	100
AISI 304	300	4,5	76	61	100
AISI 304	250	4,5	63	61	100
AISI 304	200	4,5	50	61	100
AISI 304	150	4,5	37	61	100

RELATED PRODUCTS

